

RONAK

'ALUMINIUM ELBOW' TYPE HOSE REEL DRUM

DESCRIPTION

Hose Reels are first aid firefighting equipment, meant for use by untrained/semi-trained personnel at the incipient stages of the fire. Hose Reels are strategically located at various locations, and fed by pressurized supply of water. A Thermoplastic hose of 3/4".dia. (of 30 mtrs length) is wound on the revolving drum, and connected to a discharge nozzle.

FEATURES

Leakage resistance
Premium quality
Durability
Corrosion free

GENERAL DATA

Make	RONAK.
Size/ Model	Hose Reel (Swinging type).
Inlet	3/4" MBSP Threaded connection.
Outlet	Hose fitted with Jet type shut-off nozzle. (Jet/Spray type optional).

MATERIAL OF CONSTRUCTION

Side Plates	Mild Steel IS: 513.
Hub	Mild Steel IS: 513.
Side rim	Mild Steel IS:513.
Swivel joint	Mild Steel IS:513.
Elbow	Aluminium LM6
Hose Reel tubing	Thermoplastic IS 12585.

DIMENSIONS

Plate Thickness	0.8 mm. Plate
Diameter	490 mm. Hub
Distance	165mm

TESTING AND QUALITY CONTROL

Performance Requirements

Flow: Min. 24 lpm @ 7 Bar.
Range: 6 mtrs (min).

FINISH

Plates perfectly shaped

Powder coated Fire Red Color as per IS: 5, Shade No:536

WARRANTY

12 Months from the date of supply.