



## DESCRIPTION

Hose Reels are first aid firefighting equipment, meant for use by untrained/semi-trained personnel at the incipient stages of the fire. Hose Reels are strategically located at various locations, and fed by pressurized supply of water. A Thermoplastic hose of 3/4".dia. (of 30 mtrs length) is wound on the revolving drum, and connected to a discharge nozzle.

# RONAK

## 'CHROME ELBOW' TYPE HOSE REEL DRUM

### FEATURES

Leakage resistance
Premium quality
Durability
Corrosion free

### GENERAL DATA

| | |
|---|---|
| Make | RONAK. |
| Size/ Model | Hose Reel (Swinging type). |
| Inlet | 3/4" MBSP Threaded connection. |
| Outlet | Hose fitted with Jet type shut-off nozzle. (Jet/Spray type optional). |

### MATERIAL OF CONSTRUCTION

| | |
|---|---|
| Side Plates | Mild Steel IS: 513. |
| Hub | Mild Steel IS: 513. |
| Side rim | Mild Steel IS:513. |
| Swivel joint | Mild Steel IS:513. |
| Hose Reel tubing | Thermoplastic IS 12585. |

### DIMENSIONS

Plate Thickness 0.8 mm. Plate
Diameter 490 mm. Hub
Distance 165mm

### TESTING AND QUALITY CONTROL

**Performance Requirements**
Flow: Min. 24 lpm @ 7 Bar.
Range: 6 mtrs (min).

### FINISH

Plates perfectly shaped

Powder coated Fire Red Color as per IS: 5, Shade No:536

Elbow of the drum is chrome Plated

### WARRANTY

12 Months from the date of supply.